ULTRAMAR WATER

FLEXIBILITY MEETS SUSTAINABILITY

8″ Spiral Wound Elements for Sea Water

Description:


High Rejection, High Productivity:
High pressure application for seawater treatment

Specifications:

Model	Permeate Flow GPD(m³ / day)	Active Membrane Area ft²(m²)	Stabilized Salt Rejection	Minimum Salt Rejection	Feed spacer mil(mm)	Test Conditions
SW-8040-HF	8200 (31)	400(37)	99.7%	99.6%	28(0.7)	800psi/32800ppm NaCl

1. All performance data are collected at 25° C (77°F), pH7.5 and 8% recovery rate.
2. Permeate flows for single element may vary ±15%.

Element Dimension:



Product	Dimensions – Inches (mm)		
	A	B	C
SW-8040-HF	40.0 (1016)	1.125 (29)	7.9 (201)

* 1 inch= 25.4 mm

Operating Limits for Design:

Maximum Operating Temperature	45°C(113°F)
Maximum Operating Pressure	1200psi(83bar)
Maximum Pressure Drop (single element)	15psi(1.0bar)
pH Range for Continuous Operation	2-11
pH Range for Cleaning	1.2-12
Chlorine tolerance	<0.1ppm
Maximum Feed SDI	5