ULTRAMAR WATER

FLEXIBILITY MEETS SUSTAINABILITY

8″ Spiral Wound Elements for Brackish Water

Description:


Low Pressure, High Productivity:
Low or ultra low pressure application for brackish water treatment

Specifications:

Model	Permeate Flow GPD(m^3/day)	Active Membrane Area ft^2(m^2)	Stabilized Salt Rejection	Minimum Salt Rejection	Feed spacer mil(mm)	Test Conditions
XULP-8040-440	11600(44)	440(41)	99.2%	99.0%	28(0.7)	100psi/500ppm NaCl

1. All performance data are collected at 25℃ (77 F), pH7.5 and 15% recovery rate.
2. Permeate flows for single element may vary ±15%.

Element Dimension:



Product	Dimensions – Inches (mm)		
	A	B	C
XULP-8040-440	40.0 (1016)	1.125 (29)	7.9 (201)

* 1 inch= 25.4 mm

Operating Limits for Design:

Maximum Operating Temperature…….…….…….…… 45°C(113°F)
Maximum Operating Pressure…….…….…….…….. 600psi(41bar)
Maximum Pressure Drop (single element)…….…….…… 15psi(1.0bar)
pH Range for Continuous Operation…….…….…….…….. 2-11 pH
Range for Cleaning…….…….…….…….. 2-12
Chlorine tolerance…….…….…….…….. <0.1ppm
Maximum Feed SDI…….…….…….…….…….…… 5